

LUNA

Motorized anatomic adjustable base



The base position can be adjusted as desired using the practical cable controller. This improves peripheral blood circulation, guaranteeing immediate wellbeing and improving breathing in users affected by bronchopulmonary issues. Moreover, the adjustable base allows you to find a comfortable position for resting, reading or watching TV.



The firmness adjustment sliders can be used to customize the base in the lower back area.



The shape of the protruding slat suspensions ensures the edge of the mattress is supported appropriately.




These double suspensions made of thermoplastic rubber (TPE) allow each group of slats to adjust accurately to the body shape.



The shoulder area has softer suspensions for a better shoulder embrace when sleeping on the side.

Thickened laminate frame with internal tie-rods to guarantee endurance. Flexible surface composed of 28 individual convex laminate wood slats. Slats are fitted in the frame with thermoplastic rubber (TPE) double suspensions. The base is made of five sections linked by four joints and allows the user to adjust each section according to personal comfort. The neck section is particularly useful. The fixed hip section is provided with four pairs of firmness adjustment sliders. Thinner slats are fitted in the shoulder area to accommodate the shoulder. Two harnesses prevent the mattress from slipping during movement. Solid wood tapered screw-on legs (Ø 65 mm). All wooden base components are polished, varnished with nontoxic varnish.



The robust and noiseless dual motor has a wire-connected keypad. It's an energy efficient motor, under 0.5 W in stand-by, according to the EU EcoDesign directive 2009/125/CE. It's equipped with integrated SMPS (switching-mode power supply) that reduces electromagnetic waves to a minimum. It also prevents overloads with automatic reset. An emergency battery returns the base to resting position in case of power outage. Low voltage direct current motor: 24 V DC. The keypad voltage is 24/29 DC. 2-year CE warranty.



**CLASS I
MEDICAL DEVICE
CE CERTIFIED**

Standard and non-standard heights available.



Standard height provided.

